



MATERIAL SAFETY DATA SHEET

350 RING ROAD ELIZABETHTOWN, KY 42701 (270) 769-5557 (270) 769-6418

GASKET SEALANT NO.2 PART NOS. 49302, 49311, 49343

SECTION I - PRODUCT IDENTIFICATION

Product Name : Gasket Maker #2
Product Type : Sealant

SECTION II - HAZARDOUS INGREDIENTS

<u>INGREDIENTS</u>	<u>CAS NO.</u>	<u>OSHA</u>	<u>ACGIH</u>	<u>HAZARD</u>	<u>WG%</u>
Isopropyl Alcohol	67-63-0	400	400	FLAMMABLE	7.4
1-Methoxy 2-Propanol	107-98-2	100	100	FLAMMABLE	.3
Ammonia	7664-41-7	750	750	FLAMMABLE	.3

SECTION III - NON - HAZARDOUS INGREDIENTS

<u>INGREDIENTS</u>	<u>CAS NO.</u>
Castor Oil	8001-79-4
ASP 600	1327-38-2
Calcium Carbonate	471-34-1
Lamp Black	7440-44-0
Water	

SECTION IV - CHEMICAL AND PHYSICAL PROPERTIES

Vapor Pressure : 29MM @68⁰F
Vapor Density : 2.5
Solubility in Water : .86
Specific Gravity : 1.25
Boiling Point : 170⁰F
PH : N/A
Odor : Mild
Appearance : Black Paste

SECTION V - FLAMMABILITY AND EXPLOSIVE PROPERTIES

Flash Point : 54⁰F ASTM D93-71
Method Used : Closed Cup
Explosive Limits (% by Volume in Air) : Lower - 3% Upper - 20%

Extinguishing Media	: CO ₂ , dry chemical and foam.
Hazardous Products Formed by Fire or Thermal Decomposition	: Carbon dioxide and carbon monoxide.
Unusual Fire & Explosion Hazards	: None

SECTION VI - TOXICITY AND HEALTH HAZARD DATA

Toxicity	: Eye irritant - moderately toxic by ingestion.
CARCINOGENICITY	
NTP	: No
IARC Monographs	: No
OSHA Regulated	: No
Primary Routes of Entry	: Skin, ingestion, inhalation.
Existing Conditions Aggravated by Exposure	: Vapor can be irritating to eyes, nose, throat and can cause headache, dizziness, and nausea. Liquid is an eye irritant.
EMERGENCY TREATMENT PROCEDURES:	
Ingestion	: Do not induce vomiting and get medical attention
Inhalation	: Remove to fresh air. Call a physician
Eye Contact	: Flush with water for at least 15 minutes and consult a physician.
Skin Contact	: Wash thoroughly with soap and water.
PERSONAL PROTECTION:	
Eyes	: Wear safety glasses or goggles.
Skin	: Wear rubber or plastic gloves.
Ventilation	: Sufficient to maintain vapor pressure below TLV

SECTION VIII - REACTIVITY DATA

Stability	: Stable
Hazardous Polymerization	: Will not occur.
Hazardous Decomposition Products (Non-Thermal)	: None known
Incompatibility	: Hydrofluoric acid, strong oxidizers

SECTION IX - SPILL OR LEAK AND DISPOSAL PROCEDURES

Steps to be taken in Case Of Spill or Leak	: Scrape or wipe up as much material as possible and store in a closed container. Residues may be cleaned with isopropyl alcohol. For large spills ventilate area and remove sources of ignition
Waste Disposal Method	: Dispose of this material in accordance with all federal, state and local regulations.

SECTION X - STORAGE AND HANDLING PROCEDURES

Storage : Do not store near heat, sparks or flame.
Handling : Avoid prolonged breathing of vapors and contact with eyes.

SECTION XI – HAZARD COMMUNICATION CODES

HMIS RATINGS:

Health : 1
Fire : 3
Reactivity : 0

The information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of the data or the results to be obtained from the use thereof. Because the information contained herein may be applied under conditions beyond our control, we assume no responsibility for its use.