



MATERIAL SAFETY DATA SHEET

350 RING ROAD ELIZABETHTOWN, KY 42701 (270) 769-5557 (270) 769-6418

**SLEEVELOCKER - GREEN
HIGH STRENGTH
PART NO. 49472, 49473, 49474**

SECTION I – IDENTITY INFORMATION

Product Type: Anaerobic Adhesive/Sealant

SECTION II – COMPOSITION/INFORMATION ON INGREDIENTS

<u>Hazardous Component</u>	<u>CAS Number</u>	<u>%</u>
Dimethacrylate Ester	25852-47-5	65-75
Bisphenol A Fumurate Resin	39382-25-7	20-30
Saccharin	81-07-2	1-3
Polyethylene	9002-88-4	1-3
Amorphous Silica	112945-52-5	0.1-1.0
Cumene Hydroperoxide*	80-15-9	1-3
Organic Acid	Trade Secret	0.1-1.0
Dyes	Trade Secret	0.03-0.10

*SARA Section 313 Toxic Chemical

Ingredients which have exposure limits

<u>Exposure Limits (TWA)</u>	<u>ACGIH (TLV)</u>	<u>OSHA (PEL)</u>	<u>OTHER</u>
Amorphous Silica TWA	10mg/m3 TWA	6mg/m3 TWA	3mg/m3 TWA resp. dust

Exposure Limits (STEL)

SECTION III – PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: Green liquid
Odor	: Mild
Boiling Point	: >300 ⁰ F
Vapor Pressure	: <5mmHg @ 20 ⁰ C
Vapor Density	: Approximately 3 (Air = 1)
Evaporation Rate	: N/A
Specific Gravity	: 1.04
Solubility in Water	: Negligible

SECTION IV – FIRE FIGHTING MEASURES

Flash Point	: 150-200 ⁰ F, Tag Closed Cup
Extinguishing Media	: Foam, Dry chemical or Carbon Dioxide
Unusual Fire or Explosion Hazards	: None
Special Fire Fighting Procedures	: None
Hazardous Products formed by Fire or Thermal Decomposition	: Irritating organic vapors.

SECTION V – STABILITY AND REACTIVITY DATA

Stability	: Stable
Hazardous Polymerization	: Will not occur
Incompatibility	: None

SECTION VI – HAZARDOUS IDENTIFICATION

Toxicity	: Mild eye irritant
Primary Routes of Entry	: Eyes, skin
Signs of Exposure	: May cause dermatitis on prolonged contact in sensitive individuals.
Existing Conditions Aggravated by Overexposure	: None known

FIRST AID MEASURES:

Ingestion	: Do not induce vomiting. Keep individual calm. Obtain medical attention.
Inhalation	: Does not apply.
Skin Contact	: Wash affected area with soap and water.
Eye Contact	: Flush with warm water. Seek competent medical attention.

SECTION VII – ACCIDENTAL RELEASE AND DISPOSAL MEASURES

Accidental Spill or Leak	: Soak up with inert absorbent. Store in a partly filled, closed container until disposal.
Disposal Procedures	: Incinerate or dispose of in an approved land-fill in accordance with local and EPA regulations. Not a RCRA hazardous waste.

SECTION VIII – HANDLING AND STORAGE

Safe Storage	: Store below 100 ⁰ F.
Handling	: Avoid contact with skin and eyes.

SECTION IX – PROTECTIVE EQUIPMENT

Ventilation	: Does not apply.
Respiratory Protection	: Not applicable.

Skin : Rubber, polyethylene, or neoprene gloves.
Eye Protection : Safety glasses or goggles with side shields.

SECTION X – TOXICOLOGICAL INFORMATION

See section VI

SECTION XI – ECOLOGICAL INFORMATION

No Data

SECTION XII – TRANSPORTATION INFORMATION

Domestic Ground Transport Proper Shipping Name : Unrestricted (not more than 450 liters) combustible Liquid, n.o.s. (more than 450 liters)
Hazard Class or Division : Unrestricted (not more than 450 liters) combustible Liquid (more than 450 liters)
Identification Number : None (not more than 450 liters) NA 1993 (more than 450 liters)
Marine Pollutant : No

SECTION XIII – REGULATORY INFORMATION

CA Proposition 65 : This product contains saccharin. Proper usage necessitates no Proposition 65 warning.

SECTION XIV – HAZARD CODE INFORMATION

<u>Hazard</u>	<u>NFPA Hazard Code</u>	<u>HMIS Hazard Code</u>
Health	1	1
Fire	1	1
Reactivity	1	1
Specific Hazard	None	Personal protection: See Section VIII

NFPA is a registered trademark of the National Fire Protection Association.
HMIS is a registered trademark of the National Paint and Coatings Association.

The information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of the data or the results to be obtained from the use thereof. Because the information contained herein may be applied under conditions beyond our control, we assume no responsibility for its use.

