



MATERIAL SAFETY DATA SHEET

350 RING ROAD ELIZABETHTOWN, KY 42701 (270) 769-5557 (270) 769-6418

SAFETY SOLVENT PART NO. 52155

SECTION I – IDENTITY INFORMATION

Product Name : Safety Solvent

SECTION II – HAZARDOUS INGREDIENTS

<u>INGREDIENTS</u>	<u>CAS #</u>	<u>OSHA PEL</u>	<u>ACGIH TLV</u>	<u>STEL</u>	<u>WGT %</u>
*Perchloroethylene	127-18-4	100 PPM	25 PPM	100	97.00
Carbon Dioxide	124-38-9	10000 PPM	5000 PPM		3

** Indicates Toxic Chemical(s) Subject to the Reporting Requirements of Section 313 of Title III and of 40 CFR 372.*

SECTION III – PHYSICAL DATA

Boiling Point (Range) : 250⁰F
Vapor Density : Heavier Than Air
Vapor Pressure (mm Hg @ Temp):
 Perchloroethylene : 13 - 68
 Carbon Dioxide : 38650 - 60
Solubility in Water : Nil
Specific Gravity (H₂O=1) : 1.58
Evaporation Rate : Slower Than Ether
Appearance and Odor : Aerosol Product; Colorless Liquid; Mildly Sweet.

SECTION IV – FIRE AND EXPLOSIN HAZARD DATA

FlashPoint Used) : N/A
Flammable Limits in Air by Volume : Lower - N/A Upper - N/A
Extinguishing Media : Foam, Alcohol Foam, CO₂, Dry Chemical, Water Fog.
Special Fire Fighting Procedures : Water may be used to Cool Containers To Prevent Pressure Build-Up and Explosion When Exposed to Extreme Heat. If Water is Used, Fog

Unusual Fire and Explosion Hazards

Nozzles are Preferred. Wear Goggles and Self-Contained Breathing Apparatus.
: Keep container from heat and open flame.
Closed containers may explode when exposed to extreme heat. Overexposure to decomposition products may cause a health hazard. Symptoms may not be readily apparent. Obtain Medical attention.

SECTION V – REACTIVITY DATA

Stability : Stable
Conditions to Avoid : Application to Hot Surfaces.
Incompatibility (Materials to Avoid) : Unknown.
Hazardous Decomposition or Byproducts : May Produce Fumes When Heated to Decomposition. Fumes may Contain Carbon Monoxide, Chlorine, and Hydrogen Chloride.
Hazardous Polymerization : Will Not Occur.

SECTION VI – HEALTH HAZARD DATA

Inhalation Health Risks and Symptoms
of Exposure : Respiratory Irritation, Headache, Nausea, Fatigue, Drowsiness, Impaired Co-Ordination.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE:

Skin : Contact May Dry the Skin; Prolonged Contact may Cause Irritation.

Eyes : Liquid or Vapor can irritate; Prolonged Contact May Lead to Corneal Damage.

Skin Absorption Health Risks and Symptoms
of Exposure : Not easily absorbed. Solvent action can dry and defat the skin causing the skin to crack, Leading to dermatitis.

Ingestion Health Risks and Symptoms
of Exposure : Not a likely route of exposure. If swallowed, Do not induce vomiting. Seek immediate Medical advice and/or attention.

HEALTH HAZARDS (ACUTE AND CHRONIC):

Acute : Eye Irritant. Skin Irritant. Narcotic in High Concentrations.

Chronic : Liver and Kidney Disease. Skin Irritation and Dermatitis.

CARCINOGENICITY:

NTP Carcinogen : Yes

IARC Monographs : Yes

WARNING! *This Product Contains a Chemical Known to the State of California to Cause Cancer.*

Medical Conditions Generally Aggravated by Overexposure : Acute and chronic liver and kidney disease, Anemia, coronary disease or rhythm disorders of the heart.

EMERGENCY AND FIRST AID PROCEDURES:

Inhalation : Remove to fresh air. Administer oxygen if needed. Apply artificial respiration if breathing Has stopped. Get medical attention.

Ingestion : Do Not Induce Vomiting; Call a Doctor. If Conditions Remain, Get Medical Attention.

Skin : Wipe off with towel. Wash with soap and Water. Get medical attention if irritation persists.

Eyes : Wash Immediately with Large Volumes of Fresh Water for At Least 15 Minutes. Get Medical Attention.

SECTION VII – PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be Taken if Material is Released or Spilled : Avoid breathing vapors. Ventilate area to Contain spill. Clean up area with absorbent material and place in closed containers for disposal.

Waste Disposal Method : Dispose of waste in accordance with applicable Federal, State and Local requirements. Before attempting clean up, refer to other sections of this MSDS for hazard caution information.

Precautions to Be Taken in Handling and Storing : Store and use in cool, dry, well-ventilated Areas. Avoid contact with hot metal surfaces. Keep away from excessive heat or open flame. Contents under pressure. Do Not puncture or Incinerate container or store above 120⁰F.

Other Precautions : The Storage of Non-Flammable Products with Non-Flammable Pressurizing Agent, In Cartons, Is The Same as for Ordinary Canned Goods in Cartons.

SECTION VIII – CONTROL MEASURES

Respiratory Protection : In Restricted Areas, Use Approved Chemical/Mechanical Filters Designed to

Ventilation	In Confined Areas, Use Approved AirLine Type Respirator or Hood. self-contained Breathing Apparatus is Required for Vapor Concentrations above PEL/TLV Limits. : Sufficient to prevent inhalation of solvent Vapors. General dilution and/or local exhaust Ventilation in volume or pattern to keep PEL/TLV of most hazardous ingredient below acceptable limit and LEL below stated limit.
Protective Gloves	: Solvent Resistant Required for Prolonged or Repeated Contact.
Eye Protection	: Safety Glasses with SplashGuards or Full Face Shield.
Other Protective Clothing or Equipment	: Solvent Resistant Apron.
Work/Hygienic Practices	: Eye washes and safety showers in the workplace are recommended.

SECTION IX – HAZARD COMMUNICATION CODES

HMIS RATING:

Health	: 2
Flammability	: 2
Reactivity	: 0

The Information Contained Herein is Based on Data Considered Accurate. However, No Warranty is Expressed or Implied Regarding the Accuracy of the data or the Results to be obtained From the Use Thereof. Because the Information Contained herein may be applied Under Conditions beyond Our Control, We Assume No Responsibility for Its Use.

